




tesa® 66716

Product Information



860µm d/s PU foam tape

Product Description

tesa® 66716 is a black double-sided tape consisting of a soft polyurethane foam backing equipped with black acrylic adhesive.

tesa® 66716 features

- Thickness: 860µm
- Soft and good gap-filling
- Good light blocking in XYZ direction
- Very good bonding strength
- Excellent shear performance

Application Fields

- Mounting TV screen and other large display screen to mantel or plastic frame
- Mounting on curve, uneven and rough surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PU foam	• Color	black
• Type of adhesive	modified acrylic	• Color of liner	transparent
• Type of liner	PET	• Thickness of liner	50 µm
• Total thickness	860 µm		

Properties/Performance Values

• Humidity resistance	very good	• Static shear resistance at 23°C	very good
• Softener resistance	good	• Static shear resistance at 40°C	very good

Adhesion to Values

• Steel (initial)	6 N/cm	• Steel (covered side, after 3 days)	9 N/cm
• Steel (after 3 days)	8.5 N/cm	• Steel (covered side, initial)	6.5 N/cm



tesa[®] 66716

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=66716>