

tesa® Professional Spray Glue Extra Strong

Product Information

BNR 60022

Product Description

tesa® Spray Glue Extra Strong is a spray adhesive and a fabric, wood, metal and plastic glue able to firmly bond even heavy materials with rough surfaces.

Product Features

- Suitable for heavy weight materials with rough and uneven surfaces
- Film forming spray
- Spray direction can be set either horizontal or vertical
- Adjustable spray quantity (H: high, M: medium, L: low)
- Resistant to damp and temperature from -30°C up to +80°C (short term even 100°C)
- Free from silicone

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Silicone free yes

Properties/Performance Values

•	Adhesive strength	Light adhesion	•	Reusable	no
•	Applicationfield	Office, Home	•	Solvent free	no
•	Batteries included	no	•	Suitable for children of 3 years	no
•	Batteries required	no		of age	
•	Chemical Resistance	yes	•	Suitable surfaces	Even wood, Stone,
•	Compostable	no			Brick, Acrylic glass
•	Ecofriendly packaging	no	•	Temperature resistance	yes
•	Hazard material	yes	•	Temperature resistance max.	80 °C
•	Humidity resistance	yes	•	Temperature resistance min.	-30 °C
•	Recommended distance of	30 cm	•	UV resistant	yes
	spraying		•	Washable	no
•	Residue-free removability	no	•	Waterproof	yes



tesa® Professional Spray Glue Extra Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

