



tesafilm® BASIC transparent

Product Information



BNR 58568, 58542, 58545, 58582, 58547, 58544, 58553, 58581, 58549

Product Description

tesafilm® BASIC transparent is a highly transparent multi-purpose self-adhesive tape that is ideal for office use, gift wrapping, arts and crafts.

Product Features

- Solid quality
- High transparency
- Available in several dimensions

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 41 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|--|------------------|
| • Tensile strength | 30 N/cm | • Residue-free removability | no |
| • Adhesive strength | Standard adhesion | • Reusable | no |
| • Ageing resistance (UV) | yes | • Roll width max | 19 mm |
| • Applicationfield | Office, Home | • Serrated blade | _NULL |
| • Batteries included | no | • Solvent free | yes |
| • Batteries required | no | • Suitable for right and/or left handers | _NULL |
| • Ecofriendly packaging | _NULL | • Suitable surfaces | Paper, Cardboard |
| • Hand tearability | no | • Tear resistance | no |
| • Hazard material | no | • Tensibility | 40 % |
| • Low noise unwinding | no | • Transparency | good |
| • Material | PP (polypropylene) | • Unwind force | 1.2 N/cm |
| • Max roll length | 66 m | • Writable | no |
| • Photocopy neutral | no | | |



tesafilm[®] BASIC transparent

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>