



tesa[®] Adhesive Nail Devices for Wallpaper and Plaster 0.5kg

Product Information

BNR 77782

Product Description

The adhesive nails are adjustable horizontally and vertically and thus ideal to safely mount small electric devices, e.g. Wifi-Routers, on wallpaper & plaster. Removable without a trace and reusable.

Product Features

- Horizont./vertic. adjustable adhesive nail
- For sensitive, textured surfaces (wallpaper & plaster)
- Ideal to safely mount small devices, e.g. WIFI routers
- Holds objects up to 0.5kg per nail (1kg for two nails)
- Easy On & Off: no tools, removable without trace
- Reusable with new adhesive strip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------------------|------------------|-----------------------|--------|
| • Type of adhesive | synthetic rubber | • Holding power up to | 0.5 Kg |
| • Holding power of strip up to | 0.5 Kg | • Silicone free | yes |

Properties/Performance Values

- | | | | |
|--------------------------------|------------------|-------------------------------|---------------------------------|
| • Application temperature from | -15 °C | • Residue-free removability | yes |
| • Area of use | Indoor | • Reusable | yes |
| • Batteries included | no | • Reusable with | Adhesive Strip 1kg
Wallpaper |
| • Batteries required | no | • Solvent free | yes |
| • Chemical Resistance | no | • Suitable surfaces | Wallpaper, Plaster |
| • Hazard material | no | • Temperature resistance max. | 35 °C |
| • Humidity resistance | no | • Temperature resistance min. | 5 °C |
| • Material | PS (polystyrene) | • UV resistant | no |
| • Oil and grease resistance | no | • Waterproof | no |
| • Ozone resistance | no | | |



tesa[®] Adhesive Nail Devices for Wallpaper and Plaster 0.5kg

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>